

Maryland HVAC Masters Practice Test (Sample)

Study Guide



Everything you need from our exam experts!

Copyright © 2026 by Examzify - A Kaluba Technologies Inc. product.

ALL RIGHTS RESERVED.

No part of this book may be reproduced or transferred in any form or by any means, graphic, electronic, or mechanical, including photocopying, recording, web distribution, taping, or by any information storage retrieval system, without the written permission of the author.

Notice: Examzify makes every reasonable effort to obtain accurate, complete, and timely information about this product from reliable sources.

SAMPLE

Table of Contents

Copyright	1
Table of Contents	2
Introduction	3
How to Use This Guide	4
Questions	5
Answers	8
Explanations	10
Next Steps	16

SAMPLE

Introduction

Preparing for a certification exam can feel overwhelming, but with the right tools, it becomes an opportunity to build confidence, sharpen your skills, and move one step closer to your goals. At Examzify, we believe that effective exam preparation isn't just about memorization, it's about understanding the material, identifying knowledge gaps, and building the test-taking strategies that lead to success.

This guide was designed to help you do exactly that.

Whether you're preparing for a licensing exam, professional certification, or entry-level qualification, this book offers structured practice to reinforce key concepts. You'll find a wide range of multiple-choice questions, each followed by clear explanations to help you understand not just the right answer, but why it's correct.

The content in this guide is based on real-world exam objectives and aligned with the types of questions and topics commonly found on official tests. It's ideal for learners who want to:

- Practice answering questions under realistic conditions,
- Improve accuracy and speed,
- Review explanations to strengthen weak areas, and
- Approach the exam with greater confidence.

We recommend using this book not as a stand-alone study tool, but alongside other resources like flashcards, textbooks, or hands-on training. For best results, we recommend working through each question, reflecting on the explanation provided, and revisiting the topics that challenge you most.

Remember: successful test preparation isn't about getting every question right the first time, it's about learning from your mistakes and improving over time. Stay focused, trust the process, and know that every page you turn brings you closer to success.

Let's begin.

How to Use This Guide

This guide is designed to help you study more effectively and approach your exam with confidence. Whether you're reviewing for the first time or doing a final refresh, here's how to get the most out of your Examzify study guide:

1. Start with a Diagnostic Review

Skim through the questions to get a sense of what you know and what you need to focus on. Your goal is to identify knowledge gaps early.

2. Study in Short, Focused Sessions

Break your study time into manageable blocks (e.g. 30 - 45 minutes). Review a handful of questions, reflect on the explanations.

3. Learn from the Explanations

After answering a question, always read the explanation, even if you got it right. It reinforces key points, corrects misunderstandings, and teaches subtle distinctions between similar answers.

4. Track Your Progress

Use bookmarks or notes (if reading digitally) to mark difficult questions. Revisit these regularly and track improvements over time.

5. Simulate the Real Exam

Once you're comfortable, try taking a full set of questions without pausing. Set a timer and simulate test-day conditions to build confidence and time management skills.

6. Repeat and Review

Don't just study once, repetition builds retention. Re-attempt questions after a few days and revisit explanations to reinforce learning. Pair this guide with other Examzify tools like flashcards, and digital practice tests to strengthen your preparation across formats.

There's no single right way to study, but consistent, thoughtful effort always wins. Use this guide flexibly, adapt the tips above to fit your pace and learning style. You've got this!

Questions

SAMPLE

- 1. The minimum temperature for a fire damper actuating device must be at least _____ degrees Fahrenheit.**
 - A. 120**
 - B. 140**
 - C. 160**
 - D. 180**

- 2. When installing an exhaust duct for a downflow domestic range hood, which component is required?**
 - A. Backdraft Damper**
 - B. Fire Dampers**
 - C. Duct Cap**
 - D. Noise Silencer**

- 3. What is the primary difference between direct vent and power vent in gas appliances?**
 - A. Power vent relies on an exhaust blower and may use indoor air**
 - B. Direct vent uses sealed combustion drawing outdoor air and exhausting outdoors; power vent relies on an exhaust blower and may use indoor air**
 - C. Direct vent recycles indoor air**
 - D. Power vent uses sealed combustion**

- 4. In a high-pressure boiler installation, where must shutoff valves be located?**
 - A. In the supply line only**
 - B. In the return line only**
 - C. In both the supply and return lines**
 - D. In the fuel line**

- 5. What is the function of a pressure relief valve on a boiler?**
 - A. To relieve excessive pressure to prevent boiler failure or explosion**
 - B. To regulate thermostat setpoint**
 - C. To filter the combustion gases**
 - D. To cool the boiler during startup**

- 6. ARI 700 defines what aspect of reclaimed refrigerants?**
- A. Color**
 - B. Purity**
 - C. Odor**
 - D. Viscosity**
- 7. If a circuit has 120 volts and 30 ohms resistance, the current is _____ amperes.**
- A. 2**
 - B. 3**
 - C. 4**
 - D. 5**
- 8. Which minimum vertical clearance above the floor is required for a heater installed in a public garage?**
- A. 6 feet**
 - B. 8 feet**
 - C. 10 feet**
 - D. 12 feet**
- 9. What best describes a staged or modulating burner?**
- A. A burner that cycles on and off at fixed intervals**
 - B. A burner that uses only air for combustion**
 - C. A burner that is always running at full output**
 - D. A burner that adjusts its firing rate to match load**
- 10. In a chilled water system, a connection between different metallic piping materials must be made with _____.**
- A. Dielectric fittings**
 - B. Copper couplings**
 - C. Flanged joints**
 - D. Soldered joints**

Answers

SAMPLE

1. C
2. A
3. B
4. C
5. A
6. B
7. C
8. B
9. D
10. A

SAMPLE

Explanations

SAMPLE

1. The minimum temperature for a fire damper actuating device must be at least _____ degrees Fahrenheit.

- A. 120**
- B. 140**
- C. 160**
- D. 180**

The key idea is how the temperature rating of a fire damper's actuating device determines when the damper closes to stop fire and smoke from traveling through the ductwork. The device must respond to heat quickly enough to contain a fire, but not trigger during normal operating temperatures. A rating around 160°F (about 71°C) is commonly specified because it provides a reliable balance: it's high enough to avoid nuisance closures from ordinary duct heat, yet low enough to activate early in a fire before flames and hot gases spread through the system. Lower ratings like 120°F or 140°F risk premature or unnecessary activation, while a higher rating such as 180°F could allow the fire to progress further before the damper closes. Therefore, 160 degrees Fahrenheit is used as the minimum activation temperature.

2. When installing an exhaust duct for a downflow domestic range hood, which component is required?

- A. Backdraft Damper**
- B. Fire Dampers**
- C. Duct Cap**
- D. Noise Silencer**

A backdraft damper is needed because it acts as a one-way valve in the exhaust duct, letting air flow out only when the hood is on and preventing outside air from being drawn back into the kitchen when the hood is off. This protects against drafts, odors, and energy loss in a downflow domestic range hood where the duct vents to the outdoors. Fire dampers are used where ducts pass through fire-rated protections and aren't a standard requirement for typical residential hood installations. A duct cap is an exterior termination cover, not the device that controls backflow. A noise silencer reduces sound and is optional, not a mandatory component for proper venting.

- 3. What is the primary difference between direct vent and power vent in gas appliances?**
- A. Power vent relies on an exhaust blower and may use indoor air**
 - B. Direct vent uses sealed combustion drawing outdoor air and exhausting outdoors; power vent relies on an exhaust blower and may use indoor air**
 - C. Direct vent recycles indoor air**
 - D. Power vent uses sealed combustion**

The key idea is how the appliance handles combustion air and venting. Direct vent units use sealed combustion, drawing combustion air from outside and expelling all combustion products to the outdoors. That means indoor air isn't used for the flame, and the venting is designed to bring in outside air while sending exhaust back out. Power vent adds a blower to push the exhaust through the vent to the outdoors, which helps with venting resistance and distance. However, for many power-vent configurations, the appliance can still rely on indoor air for combustion rather than pulling it from outside. So the main distinction is that direct vent is sealed and uses outdoor air for combustion, while power vent centers on the exhaust fan and may allow indoor air to be used for combustion.

- 4. In a high-pressure boiler installation, where must shutoff valves be located?**
- A. In the supply line only**
 - B. In the return line only**
 - C. In both the supply and return lines**
 - D. In the fuel line**

Isolating a high-pressure boiler safely requires stopping flow on both sides of the boiler. Placing shutoff valves in both the supply and return lines lets you completely isolate the boiler from the piping system for service, testing, or emergencies. If you only close the valve in the supply line, the return line can still circulate water back to the boiler, keeping it pressurized and hot. If only the return line is shut, the supply can still feed the boiler. A single valve cannot fully de-energize the boiler and make it safe to work on. The fuel shutoff stops fuel, but it does not prevent water/steam flow, so valves on both lines are needed to ensure complete isolation.

5. What is the function of a pressure relief valve on a boiler?

- A. To relieve excessive pressure to prevent boiler failure or explosion**
- B. To regulate thermostat setpoint**
- C. To filter the combustion gases**
- D. To cool the boiler during startup**

A pressure relief valve is a safety device that opens when the boiler system pressure rises above its designed limit, venting steam or hot water to reduce pressure and prevent boiler failure or explosion. Once the pressure falls back below the reset point, it reseals and continues protecting the system. It's not responsible for thermostat control, filtering combustion gases, or cooling the boiler during startup—those tasks are handled by other components. Regular testing and maintenance ensure it will operate correctly when needed.

6. ARI 700 defines what aspect of reclaimed refrigerants?

- A. Color**
- B. Purity**
- C. Odor**
- D. Viscosity**

Purity is the focus. ARI 700 defines what counts as reclaimed refrigerant by setting strict purity requirements. The reason this matters is that contaminants such as moisture, acids, oil carryover, and noncondensables can damage compressors, degrade lubricants, reduce efficiency, and shorten system life. By specifying acceptable impurity levels and the methods to test them, ARI 700 ensures reclaimed refrigerants are clean enough for safe reuse. Color, odor, and viscosity aren't used by this standard to determine reclaim eligibility, because they're unreliable indicators of overall cleanliness and performance.

7. If a circuit has 120 volts and 30 ohms resistance, the current is _____ amperes.

- A. 2**
- B. 3**
- C. 4**
- D. 5**

Using Ohm's Law, current equals voltage divided by resistance: $I = V / R$. With 120 volts and 30 ohms, $I = 120 / 30 = 4$ amperes. This checks out because $30 \Omega \times 4 \text{ A} = 120 \text{ V}$. If you used 2 A, 3 A, or 5 A, you'd need 60 Ω , 40 Ω , or 24 Ω respectively to maintain 120 V, which is not the given resistance. So the current is 4 amperes.

8. Which minimum vertical clearance above the floor is required for a heater installed in a public garage?

- A. 6 feet**
- B. 8 feet**
- C. 10 feet**
- D. 12 feet**

In garages that are open to the public, safety relies on keeping heat sources away from floor-level hazards. Gasoline and other flammable liquids often sit or spill on the floor, and their vapors tend to stay near the bottom. By locating a heater with a minimum vertical clearance of eight feet above the floor, the hot surface is kept well above most floor-level vapors, reducing the risk that vapors could reach ignition sources. It also helps protect the unit from damage or accidental impact from vehicles and allows space for maintenance and proper ventilation around the heater. For these safety and practical reasons, eight feet is the required height.

9. What best describes a staged or modulating burner?

- A. A burner that cycles on and off at fixed intervals**
- B. A burner that uses only air for combustion**
- C. A burner that is always running at full output**
- D. A burner that adjusts its firing rate to match load**

Staged or modulating burners adjust heat output to match the current load instead of running at a single fixed power. In staged systems, the burner can operate at multiple levels; in true modulation, the firing rate changes continuously to maintain the target temperature or heat input. This control method improves efficiency, reduces fuel use, minimizes temperature swings, and lowers wear from frequent cycling. It also often reduces emissions compared to full-on operation. The other options describe fixed on/off cycling, using air without modulation, or always running at full output, none of which capture the idea of varying the firing rate to meet demand. Therefore, the best description is a burner that adjusts its firing rate to match load.

10. In a chilled water system, a connection between different metallic piping materials must be made with _____.

- A. Dielectric fittings**
- B. Copper couplings**
- C. Flanged joints**
- D. Soldered joints**

Connecting different metallic piping materials in a chilled water system must provide electrical isolation between the metals to prevent galvanic corrosion. Dielectric fittings accomplish this by placing insulating materials between the different metals, so the water cannot carry electrical current directly between them. This keeps the more anodic metal from corroding and prevents leaks that result from accelerated corrosion over time. Without isolation, a copper-to-steel or cast iron-to-copper joint would set up a galvanic couple in the presence of the circulating water electrolyte, leading to premature failure. Dielectric fittings are specifically designed for this purpose and are common wherever two different metals must be joined in HVAC piping. Other joining methods like copper couplings, soldered joints, or standard flanged joints create or maintain a conductive metal path between dissimilar metals, so they are not appropriate for preventing galvanic corrosion in this scenario.

SAMPLE

Next Steps

Congratulations on reaching the final section of this guide. You've taken a meaningful step toward passing your certification exam and advancing your career.

As you continue preparing, remember that consistent practice, review, and self-reflection are key to success. Make time to revisit difficult topics, simulate exam conditions, and track your progress along the way.

If you need help, have suggestions, or want to share feedback, we'd love to hear from you. Reach out to our team at hello@examzify.com.

Or visit your dedicated course page for more study tools and resources:

<https://mdhvacmasters.examzify.com>

We wish you the very best on your exam journey. You've got this!

SAMPLE